



Shenzhen Heijin Industrial Manufacturing Co., Ltd
C901 Silver Star Technology Building, No1301, Guanlan Street,
Longhua New District, Shenzhen, China.
Contact : Nancy Email: Nancy@edu-solution.com.cn
Tel/whatsapp: 86 18137271771

Motherboard		RK3576			
Product Specification		65"	75"	86"	98"
OC	Panel Model	HJ-TD65	HJ-TD75	HJ-TD86	HJ-TD86
	Zero Bonding	Zero Bonding	Zero Bonding	Zero Bonding	Zero Bonding
Display	Response Time	6.5ms (typ.)	6.5ms (typ.)	6.5ms (typ.)	6.5ms (typ.)
	Aspect Ratio	16:9	16:9	16:9	16:9
	Display Area	1430 (H) x805(V) mm	1653(H) x 930.2(V) mm	1895.2(H) x 1065.6 (V) mm	2158.8(H)x1215(V)mm
	Dimension	1489.3x948.53x84.5mm(L*H*W)	1714.5x1074.3x89mm(L*H*W)	1963.5x1179.7x93.4mm(L*H*W)	2212.3mm*1303mm*103.9mm(L*H*W)
	Resolution	3840x2160 (4k@60hz)	3840x2160 (4k@60hz)	3840x2160 (4k@60hz)	3840x2160 (4k@60hz)
	Pixel Pitch	0.372 (W)x0.372(H)	0.429.6(H) x0.4296(V)	0.4935(W) x 0.4935(H)	0.4935(W) x 0.4935(H)
	Refreshing Frequency	60HZ	60HZ	60HZ	120HZ
	Display Color	10bit, 1.07B	10bit, 1.07B	10bit, 1.07B	10bit, 1.07B
	Contrast Ratio (static)	1200: 1	1200: 1	1200: 1	1200: 1
	Contrast Ratio (dynamic)	6000: 1	6000: 1	6000: 1	6000: 1
Android System	Viewing Angle	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)
	Back Light Unit	D-LED	D-LED	D-LED	D-LED
	Brightness with glass	550cd/m2±10%	550cd/m2±10%	550cd/m2±10%	550cd/m2±10%
	Life Time	50,000 H	50,000 H	50,000 H	50,000 H
Touch System	Chipset	RK3576			
	System Version	Android 16.0			
	CPU	A72*4 (MAX: 2.2GHz)+Cortex A53*4 (MAX: 2.0GHz)			
	GPU	ARM Mali G52 MC3 GPU (MAX: 900MHz)			
	RAM	16GB			
Speaker	ROM	256GB			
	Sensing Type	Infrared technology (IR)			
	Glass Surface Technology	Anti-Glare + Anti-Fingerprint + Anti-microbial Tempered Glass			
	Touch point	Windows system: 50 TOUCH; Android system: 20 TOUCH			
	System	Support Windows, Mac, Android , Linux, Chrome			
Built-in Camera	Touch Tool	Finger or pen			
	Response Time	≤5ms			
	Touch accuracy	1mm			
	Touch stroke speed	2m/s			
Mic	Interpolation Resolution	32767 X 32767			
	NFC	support(NFC screen mirroring)			
	Sound Channel	Front panel built-in x2			
	Output Power	20W x2			
Built-in Camera	Subwoofer	20W			
	Quantity	8MIC(Optional)			
	Voice Pickup Distance	Optional			
	Connection	Default no camera (Built-in Or external USB device)			
Bluetooth	Resolution	Default no camera (48mp Optional)			
	Location	Default no camera (in the middle of top frame or external USB device)			
	Version	5.2			
	Working Frequency	2.4Ghz			
Wi-Fi	Working Distance	<20M			
	Version	802.11a/b/g/n/ac/ax (wifi6)			
	Working Frequency	2.4G +5G			
	Working Distance	<20M			
Environmental Conditions	Operation Temperature	0 °C~ 45 °C			
	Operation Humidity	10% ~90%			
	Storage Temperature	-20 °C~ 60 °C			
	Storage Humidity	10% ~90%			
Power	Power Requirements	100-240V, 50/60Hz	100-240V, 50/60Hz	100-240V, 50/60Hz	100-240V, 50/60Hz
	Rated consumption(W)	≤79W	≤89W	≤119W	≤240W
	Standby Power	≤ 0.5W	≤ 0.5W	≤ 0.5W	≤ 0.5W
Front I/O port	HDMI IN	1	1	1	1
	Touch USB	1	1	1	1
	TYPE-C (Front)	1 (full functions , 15w PD)	1 (full functions , 15w PD)	1 (full functions , 15w PD)	1 (full functions , 15w PD)
	USB3.0 (Front)	3	3	3	3
	HDMI IN1.4			/	
	HDMI IN2.0			3	
	HDMI OUT2.0			1	
	USB2.0			1	
	USB3.0			2	
	Type c in			full function100w x1	
Rear I/O Port	Type c out			1 (no PD, 4K@60Hz);	
	MIC IN			1	
	Earphone/line out			1(3.5mm)	
	TOUCH USB 3.0			3	
	SPDIF / Coax			1*SPDIF	

	RS232	1			
	RJ45 IN	1 (1000M)			
	RJ45 OUT	1 (1000M)			
	SD Card / TF Card	1			
	DP IN	1(DP 1.4b, HDCP 1.3/2.3,4K@60Hz)			
	VGA	1			
	VGA Audio In	1			
Packaging & Structure	OPS solt	198*180*30 &120x180x30mm(Optional)			
	Packing size	1650x1000x200mm(L*H*W)	1875x1020x200mm(L*H*W)	2070x1300x200mm(L*H*W)	2350x1400x235mm(L*H*W)
	N.W.	37kg±1	49kg±1	67kg±1	90kg±1
	G.W.	49kg±2	62kg±2	82kg±2	108kg±2
	VESA Mount	300mm*400mm	500mmx600mm	600mm*600mm	400mmx800mm
Accessories	Pen holder	2	2	2	2
	Remote control	1			
	Power Cabel	3mx1			
	HDMI Cabel	3mx1			
	Touch Cabel	3mx1			
	Writing Pen	2			
	Wall mount	1			